

CUSTOMER EMAIL: _____

OVERALL LENGTH _____

BACKANGLE _____

IF MOLY IS NOT SPECIFIED, STANDARD MOLY LENGTHS WILL BE USED

MOLY START: _____ MOLY LENGTH: _____

the moly start position is measured as the distance from the combustion face to the guide when the valve is closed.

HEAD DIA.
Ø _____

R _____

Ø STEM DIAMETER _____ TIP LENGTH _____

GROOVE TYPE

PLEASE CHECK

TIP OPTIONS

PLEASE CHECK

SQUARE

WITH HARD TIP

BEAD LOC (.055"R)

MINIMUM TIP LENGTH FOR HARD TIP IS .290" ON TITANIUM VALVES

RADIUS _____

WITHOUT HARD TIP

_____ @ _____
2ND BACKCUT WIDTH & ANGLE

_____ @ _____
1ST BACKCUT WIDTH & ANGLE

_____ @ _____
SEAT WIDTH & ANGLE

DISHED FACE : YES NO ANGLE: _____ RIM WIDTH: _____

MARGIN _____

WEAR COATING OPTION: NO COATING (Moly Only)

CrN Valve

PROPRIETARY AND CONFIDENTIAL

CUSTOMER: _____

CONTACT PHONE: _____

DATE: ____/____/____ NEED BY: ____/____/____

PURCHASE ORDER # _____

QUANTITY NEEDED: _____

MATERIAL CHOICE:

TITANIUM

STAINLESS STEEL

INCONEL

APPLICATION OF USE

N/A NITROUS TURBO BLOWER

CUSTOM VALVE ORDER FORM



PH: 704-799-1955
FX: 704-799-1956

WWW.TITANIUMVALVE.COM